SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : ANYCUBIC

3D Printing ECO UV Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer use
Use of the substance/mixture : 3D printer filaments

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Shenzhen Anycubic Technology Co., Ltd Room 101-501, Building No. 11, Yinhai Industrial Park, Yinhe Community, Yuanshan Street 518000 Longgang District, Shenzhen, Guangdong - China T 15002066159

xiexiaona@anycubic.com

1.4. Emergency telephone number

Emergency number : 15112413757

Only available during office hours.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, 24/7, healthcare professionals only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1 H317 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

Full text of H-statements: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07



GHS09

Signal word : Warnin

Hazardous ingredients : isooctyl acrylate; 2-[[2,2-bis[[(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-

propanediyl diacrylate

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children. P261 - Avoid breathing vapours.

P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P391 - Collect spillage.

P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

Other hazards : Results of PBT and vPvB assessment : Not applicable.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Fatty acids, soya, epoxidized, Bu esters	(CAS-No.) 71302-80-2	45	Not classified

SAFETY DATA SHEET	Page: 3 / 15 Revision nr: 1.0 Issue date: 16/06/2021
ANYCUBIC 3D Printing ECO UV Resin	Supersedes :

isooctyl acrylate	(CAS-No.) 29590-42-9 (EC-No.) 249-707-8 (EC Index) 607-244-00-2	30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-[[2,2-bis[[(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate	(CAS-No.) 94108-97-1 (EC-No.) 302-434-9	15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
2-hydroxy-1-(4-(4-(2-hydroxy-2-methylpropionyl)benzyl)phenyl)-2-methylpropan-1-one	(CAS-No.) 474510-57-1 (EC-No.) 444-860-9 (EC Index) 606-140-00-4	5	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Polychloro copper phthalocyanine	(CAS-No.) 1328-53-6 (EC-No.) 215-524-7 (EC Index) -	5	Not classified

Specific concentration limits:

Substance name	Product identifier	Specific concentration limits
isooctyl acrylate	(CAS-No.) 29590-42-9 (EC-No.) 249-707-8	(10 ≤C < 100) STOT SE 3, H335
	(EC Index) 607-244-00-2	

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice

: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a

physician. Show this safety data sheet to the doctor in attendance.

Inhalation : Remove casualty to fresh air and keep warm and at rest. Give oxygen or

artificial respiration if necessary. In case of doubt or persistent symptoms,

consult always a physician.

Skin contact : Remove contaminated clothing and shoes. Gently wash with plenty of soap

and water. In case of doubt or persistent symptoms, consult always a

physician.

Eyes contact : Rinse immediately carefully and thoroughly with eye-bath or water. Remove

contact lenses, if present and easy to do. Continue rinsing. In case of doubt or

persistent symptoms, consult always a physician.

Ingestion : Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : May cause respiratory irritation. The following symptoms may occur:

Headache. Nausea. Irritation.

Skin contact : May cause an allergic skin reaction. Causes skin irritation. The following

symptoms may occur: Redness, pain.

Eyes contact : Causes serious eye irritation. The following symptoms may occur: Redness,

pain.

Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Not flammable. Heating will cause a rise in pressure with a risk of bursting.

Hazardous decomposition products in

case of fire

: Carbon oxides (CO, CO2).

5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain

the extinguishing fluids by bunding. Prevent fire fighting water from entering

the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-

contained breathing apparatus.

Other information : Do not allow run-off from fire-fighting to enter drains or water courses.

Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel

: Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

6.1.2. For emergency responders

For emergency responders

: Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Contaminated work clothing must not be allowed out of the workplace. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures

: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Keep out of the reach of children.

Storage conditions

: Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.

Heat and ignition sources

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight.

Special rules on packaging

: Containers which are opened should be properly resealed and kept upright to

prevent leakage. Keep container tight closed.

Packaging materials

: Keep only in the original container.

7.3. Specific end use(s)

3D printer filaments.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information

: Recommended monitoring procedures :. Personal air monitoring. Room air monitoring

8.2. Exposure controls

Engineering measure(s)

: Organisational measures to prevent /limit releases, dispersion and exposure. See Section 7 for information on safe handling. Use only outdoors or in a well-ventilated area.

Personal protective equipment

: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hand protection

Wear chemically resistant gloves (tested to EN374). Suitable material: Not determined. Thickness: Not determined. Breakthrough time: Not determined. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Eye protection

: Use suitable eye protection (EN166): goggles

Body protection

: Wear suitable protective clothing

Respiratory protection

: In case of insufficient ventilation, wear suitable respiratory equipment. Halfface mask (DIN EN 140). full face mask (DIN EN 136). Filter type: (ABEK) (EN14387). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)

Thermal hazard protection

: Not required for normal conditions of use. Use dedicated equipment.

Environmental exposure controls

: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SAFETY DATA SHEET	Page : 6 / 15
G. 11 _ 1 . 1 . 2 . 1 . 1 . 1 . 1 . 1 . 1 . 1 .	Revision nr : 1.0
	Issue date : 16/06/2021
ANYCUBIC	Supersedes :
3D Printing ECO UV Resin	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : pink.
Odour : slight.

Odour threshold : No data available : No data available Relative evaporation rate (butylacetate=1) : No data available Melting / freezing point : No data available Freezing point : No data available Initial boiling point and boiling range : No data available Flash point : No data available Auto-ignition temperature : Not self-igniting Decomposition temperature : No data available Flammability (solid, gas) : Not applicable, liquid : No data available Vapour pressure Vapour density : No data available Relative density : No data available Solubility : No data available. Partition coefficient n-octanol/water : No data available

Explosive properties : Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the

molecule.

: No data available: No data available

Oxidising properties : Not applicable. The classification procedure needs not to be applied because

there are no chemical groups present in the molecule which are associated

with oxidising properties.

Explosive limits No data available Particle size : Not applicable Particle size distribution : Not applicable Particle shape : Not applicable Particle aspect ratio : Not applicable Particle aggregation state : Not applicable Particle agglomeration state : Not applicable Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2. Other information

Kinematic viscosity

Dynamic viscosity

9.2.1. Information with regard to physical hazard classes

No additional information available

SAFETY DATA SHEET	Page : 7 / 15
	Revision nr : 1.0
	Issue date : 16/06/2021
ANYCUBIC	Supersedes :
3D Printing ECO UV Resin	
02 : ::::::::: 1	

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. See Section 7 for information on safe handling.

10.5. Incompatible materials

Strong oxidizing agents. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

isooctyl acrylate (29590-42-9)		
LD50/oral/rat	> 5 g/kg	
LD50/dermal/rabbit	> 2000 mg/kg	
2-hydroxy-1-(4-(4-(2-hydroxy-2-methylp	ropionyl)benzyl)phenyl)-2-methylpropan-1-one (474510-57-1)	
LD50/dermal/rat	> 2000 mg/kg	
Polychloro copper phthalocyanine (132	8-53-6)	
LD50/oral/rat	> 5000 mg/kg	
Skin corrosion/irritation	: Causes skin irritation.	
	pH: No data available	
Serious eye damage/irritation	: Causes serious eye irritation.	
	pH: No data available	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)	
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)	
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)	
STOT-single exposure	: May cause respiratory irritation.	
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)	
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)	

ANYCUBIC 3D Printing ECO UV Resin		
Kinematic viscosity	No data available	

Other information

: Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: Not applicable

11.2.2 Other information

Other information

: Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment,

short-term (acute)

: Very toxic to aquatic life.

Hazardous to the aquatic environment,

long-term (chronic)

: Very toxic to aquatic life with long lasting effects.

isooctyl acrylate (29590-42-9)	,1	
LC50 - Fish [1]	0,67 mg/l (Exposure time: 96 h - Species: Pimephales promelas)	
EC50 - Crustacea [1]	0,4 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
2-hydroxy-1-(4-(4-(2-hydroxy-2-methylpropionyl)benzyl)phenyl)-2-methylpropan-1-one (474510-57-1)		
LC50 - Fish [1]	3,5 mg/l (Exposure time: 96 h - Species: Danio rerio [static])	
Polychloro copper phthalocyanine (1328-53-6)		
LC50 - Fish [1]	752,4 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	

12.2. Persistence and degradability

ANYCUBIC 3D Printing ECO UV Resin		
Persistence and degradability	No additional information available.	

12.3. Bioaccumulative potential

ANYCUBIC 3D Printing ECO UV Resin		
Partition coefficient n-octanol/water	No data available	
Bioaccumulative potential	No additional information available.	

isooctyl acrylate (29590-42-9)	
BCF - Fish [1]	(no bioaccumulation expected)

SAFETY DATA SHEET Page : 9 / 15 Revision nr : 1.0 Issue date : 16/06/2021 ANYCUBIC Supersedes :

Polychloro copper phthalocyanine (1328-53-6) BCF - Fish [1] 0,51 - 74

3D Printing ECO UV Resin

12.4. Mobility in soil

ANYCUBIC 3D Printing ECO UV Resin	
Mobility in soil	No data available

12.5. Results of PBT and vPvB assessment

ANYCUBIC 3D Printing ECO UV Resin		
Results of PBT assessment	Not applicable	

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: Not applicable

12.7. Other adverse effects

Other adverse effects : No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Do not pierce or burn, even after use. Never use pressure to empty container.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC)

This material and its container must be disposed of as hazardous waste Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID		
14.1. UN number	14.1. UN number					
3082	3082	3082	3082	3082		
14.2. UN proper ship	ping name					
ENVIRONMENTALLY	ENVIRONMENTALLY	Environmentally	ENVIRONMENTALLY	ENVIRONMENTALLY		
HAZARDOUS	HAZARDOUS	hazardous substance,	HAZARDOUS	HAZARDOUS		
SUBSTANCE, LIQUID,	SUBSTANCE, LIQUID,	liquid, n.o.s. (isooctyl	SUBSTANCE, LIQUID,	SUBSTANCE, LIQUID,		
N.O.S. (isooctyl	N.O.S. (isooctyl	acrylate ; 2-hydroxy-1-	N.O.S. (isooctyl	N.O.S. (isooctyl		
acrylate ; 2-hydroxy-1-	acrylate; 2-hydroxy-1-	(4-(4-(2-hydroxy-2-	acrylate ; 2-hydroxy-1-	acrylate ; 2-hydroxy-1-		
(4-(4-(2-hydroxy-2-	(4-(4-(2-hydroxy-2-	methylpropionyl)benz	(4-(4-(2-hydroxy-2-	(4-(4-(2-hydroxy-2-		
methylpropionyl)benz	methylpropionyl)benz	yl)phenyl)-2-	methylpropionyl)benz	methylpropionyl)benz		
yl)phenyl)-2-	yl)phenyl)-2-	methylpropan-1-one)	yl)phenyl)-2-	yl)phenyl)-2-		
methylpropan-1-one)	methylpropan-1-one)		methylpropan-1-one)	methylpropan-1-one)		

SAFETY DATA SHEET

Page: 10 / 15

Revision nr: 1.0

Issue date: 16/06/2021

ANYCUBIC 3D Printing ECO UV Resin

Supersedes:

ADR	IMDG	IATA	ADN	RID		
Transport document description						
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (isooctyl acrylate; 2-hydroxy-1- (4-(4-(2-hydroxy-2- methylpropionyl)benz yl)phenyl)-2- methylpropan-1-one), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (isooctyl acrylate; 2-hydroxy-1- (4-(4-(2-hydroxy-2- methylpropionyl)benz yl)phenyl)-2- methylpropan-1-one), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (isooctyl acrylate; 2-hydroxy-1- (4-(4-(2-hydroxy-2- methylpropionyl)benz yl)phenyl)-2- methylpropan-1-one), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (isooctyl acrylate; 2-hydroxy-1- (4-(4-(2-hydroxy-2- methylpropionyl)benz yl)phenyl)-2- methylpropan-1-one), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (isooctyl acrylate; 2-hydroxy-1- (4-(4-(2-hydroxy-2- methylpropionyl)benz yl)phenyl)-2- methylpropan-1-one), 9, III		
14.3. Transport haza				1		
9	9	9	9	9		
14.4. Packing group						
III	III	III.	III	III		
14.5. Environmental hazards						
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes		
	No supplementary information available					

Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) M6

Special provisions 274, 335, 375, 601

Limited quantities (ADR) Excepted quantities (ADR)

P001, IBC03, LP01, R001 Packing instructions (ADR)

Special packing provisions (ADR) PP1 Mixed packing provisions (ADR) MP19 Portable tank and bulk container T4 instructions (ADR)

Portable tank and bulk container

special provisions (ADR)

TP1, TP29

Tank code (ADR) **LGBV** Vehicle for tank carriage AT Transport category (ADR) 3 Special provisions for carriage -V12

Packages (ADR)

SAFETY DATA SHEET

Page: 11 / 15

Revision nr: 1.0

Issue date: 16/06/2021

ANYCUBIC 3D Printing ECO UV Resin

Supersedes:

Special provisions for carriage -Loading, unloading and handling

(ADR)

Hazard identification number (Kemler

No.)

Orange plates

90

CV13

90

3082

Tunnel restriction code EAC code •3Z

- Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1

: LP01, P001 Packing instructions (IMDG)

: PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29 EmS-No. (Fire) : F-A : S-F EmS-No. (Spillage) Stowage category (IMDG)

- Air transport

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y964 PCA limited quantity max net quantity : 30kgG

(IATA)

PCA packing instructions (IATA) : 964 PCA max net quantity (IATA) : 450L CAO packing instructions (IATA) : 964 CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

- Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L Excepted quantities (ADN) : E1 : PP Equipment required (ADN) Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L

Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container : T4

instructions (RID)

Portable tank and bulk container special : TP1, TP29

provisions (RID)

Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage - : W12

Packages (RID)

Special provisions for carriage - : CW13, CW31

Loading, unloading and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	ANYCUBIC 3D Printing ECO UV Resin
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes	ANYCUBIC
or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	3D Printing ECO UV Resin

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4510.text	Dangereux pour l'environnement aquatique de catégorie aiguë 1 ou chronique 1.		
4510.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 100 t. Quantité seuil haut au sens de l'article R. 511-10 : 200 t.	A	1
4510.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 20 t mais inférieure à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 100 t. Quantité seuil haut au sens de l'article R. 511-10 : 200 t.	DC	

Germany

Page: 13 / 15 **SAFETY DATA SHEET** Revision nr: 1.0 Issue date: 16/06/2021 Supersedes: **ANYCUBIC** 3D Printing ECO UV Resin

Regulatory reference

: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

German storage class (LGK)

: LGK 12 - Non-combustible liquids

Hazardous Incident Ordinance (12.

: Listed in the 12. BlmSchV (Annex I) under: 1.3.1

BImSchV)

Quantity threshold for operational area under § 1 para. 1

Sentence 1: 100000 kg Sentence 2: 200000 kg

Netherlands

Waterbezwaarlijkheid

: A (1) - zeer vergiftig voor in water levende orga-nismen kan in aquatische

milieu op lange termijnschadelijke effecten veroorzaken

SZW-lijst van kankerverwekkende stoffen

: None of the components are listed

SZW-lijst van mutagene stoffen NIET-limitatieve lijst van voor de : None of the components are listed

voortplanting giftige stoffen -Borstvoeding

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen -Vruchtbaarheid

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen -

: None of the components are listed

Ontwikkeling

Denmark

Recommendations Danish Regulation

: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Chemical safety assessment

Not applicable

SECTION 16: Other information

Abbreviations and acronyms:

ABM = Algemene beoordelingsmethodiek
ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Code
LEL = Lower Explosive Limit/Lower Explosion Limit UEL = Upper Explosion Limit/Upper Explosive Limit REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
BTT = Breakthrough time (maximum wearing time)
DMEL = Derived Minimal Effect level
DNEL = Derived No Effect Level
EC50 = Median Effective Concentration
EL50 = Median effective level
ErC50 = EC50 in terms of reduction of growth rate
ErL50 = EL50 in terms of reduction of growth rate

SAFETY DATA SHEET	Page: 14 / 15
	Revision nr : 1.0
	Issue date : 16/06/2021
ANYCUBIC	Supersedes :
3D Printing ECO UV Resin	
02 : :g 200 0 t 1.00	

EWC = European waste catalogue
LC50 = Median lethal concentration
LD50 = Median lethal dose
LL50 = Median lethal level
NA = Not applicable
NOEC = No observed effect concentration
NOEL: no-observed-effect level
NOELR = No observed effect loading rate
NOAEC = No observed adverse effect concentration
NOAEL = No observed adverse effect level
N.O.S. = Not Otherwise Specified
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
PNEC = Predicted No Effect Concentration
Quantitative structure-activity relationship (QSAR)
STOT = Specific Target Organ Toxicity
TWA = time weighted average
VOC = Volatile organic compounds
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the : ECHA (European Chemicals Agency). LOLI. Supplier information.

datasheet

: Training staff on good practice. Manipulations are to be done only by qualified

and authorised persons.

Other information

Training advice

: Classification - Assessment method: CLP Calculation method (Article 9).

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Classification according to Regulation (EC) No. 1272/2008 [CLP] Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our

SAFETY DATA SHEET	Page: 15 / 15
	Revision nr : 1.0
	Issue date : 16/06/2021
ANYCUBIC	Supersedes :
3D Printing ECO UV Resin	

knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

